



EN 1092-1-01 PN10

Roscada

Según EN 10226-1 (ISO 7/1)

DIN 2576 - PN10

Acero Inoxidable 1.4307 / A-304L

Acero Inoxidable 1.4404 / A-316L

Tipo A (cara plana)

Código		DN	Tubo d1	Brida				Tornillo			Peso kg/u.	
AISI 304L	AISI 316L			Rp	D	Ci	K	Cant.	Rosca	L		
352BR015	354BR015	PN 10	15	21,3	1/2"	95	14	65	4	M12	14	0,669
352BR020	354BR020		20	26,9	3/4"	105	16	75	4	M12	14	0,936
352BR025	354BR025		25	33,7	1"	115	16	85	4	M12	14	1,110
352BR032	354BR032		32	42,4	1.1/4"	140	(16) 18	100	4	M16	18	1,620
352BR040	354BR040		40	48,3	1.1/2"	150	(16) 18	110	4	M16	18	1,860
352BR050	354BR050		50	60,3	2"	165	(18) 20	125	4	M16	18	2,470
352BR065	354BR065		65	76,1	2.1/2"	185	(18) 20	145	(4) 8	M16	18	3,000
352BR080	354BR080		80	88,9	3"	200	20	160	8	M16	18	3,790
352BR100	354BR100		100	114,3	4"	220	(20) 22	180	8	M16	18	4,030

(*) Medidas entre paréntesis según norma DIN 2576 PN10