

# E-mini instant water heater MCX



## Application areas

Single point supply:

- > Washbasin
- > Sanitary facilities in commercial buildings
- > Kitchenette (MCX 6 or MCX 7)



# E-mini instant water heater

## MCX

### Product information



Energy efficiency class <b>A</b> (Scale: A+ to F)	MCX3		MCX4		MCX6		MCX7	
	Part number:	1500-15003	1500-15004	1500-15006	1500-15007			
Type:	closed-outlet							
Maximum operating pressure [MPa (bar)]:	1 (10)							
Water connections (thread connections):	G $\frac{3}{8}$ "							
User set temperature [°C]:	> 35 – 38 – 45							
Hot water output at $\Delta t = 25\text{ K}$ <sup>1)</sup> [l/min]:	2.0	2.5	3.3	3.7				
Switch-on flow rate / max. flow rate <sup>2)</sup> [l/min]:	1.2 / 2.0	1.5 / 2.5	1.5 / 3.3	1.5 / 3.7				
Nominal power rating [kW]:	3.5	4.4	5.7	6.5				
Supply voltage [1~ / N / PE 220 – 240 V AC]:	☺ with plug <sup>3)</sup>	☑ permanent connection	☑ permanent connection					
Supply voltage [2~ / PE 400 V AC]:							☑ permanent connection	
Nominal current [A]:	15	19	25	16				
Required cable diameter [mm <sup>2</sup> ]:	1.5	2.5	4.0	2.5				
Bare wire heating system IES <sup>®</sup> :	✓							
Ready for Smart Control:	✓ ☑ (optional)							
Ready for FX wireless remote control:	✓ 📶 (optional)							
Solar-compatible, suitable for reheating (inlet temperature $\leq 70\text{ °C}$ ):	✓ ☀️							
VDE approved / Protection class:	✓ / IP 25							
Specific water resistance at 15 °C [ $\Omega\text{cm}$ ] $\geq$ :	1100	800	800	1100				
Nominal volume [litres]:	0.2							
Weight filled with water [kg]:	approx. 1.5							
Dimensions (height × width × depth) [cm]:	13.5 × 18.6 × 8.7							

1) Temperature increase e.g. from 15 °C to 40 °C 2) Limited flow amount for optimal temperature increase. Can be adjusted via water amount adjustment. 3) Also available as MCX3 (E) [part no.: 1500-15013] with power supply cable for permanent connection.


#### Description

- > Electronically controlled instant water heater (undersink model) with a compact design for energy-efficient hot water supply of a washbasin or a kitchenette
- > The heating output is electronically controlled. This provides an ideal hot water temperature without the need to add cold water at the tap.
- > Touch button controls with colour LEDs to set the outlet temperature to 35 °C, 38 °C or max. 45 °C
- > The efficient bare wire heating system IES<sup>®</sup> with replaceable heating cartridge provides an extended service life and easy maintenance
- > Unvented design
- > Connection kit (T-piece and flexible pressure hose) for an angle valve is included
- > Aerator insert for tap adapter M 22/24 at the tap is included
- > Can also be controlled via tablet or smartphone (iOS 9\* or higher / Android-OS 4.4 or higher, FXE adapter, CLAGE Home Server and the »Smart Control« app required)

#### Profitability comparison (Source: www.clage.com)

**Saves up to 85 % energy compared to conventional small storage heaters.**

The E-compact instant water heater features an economical operation. The water is heated directly as it flows through the unit. Hot water is not stored in a tank, which saves standby energy that would be otherwise required.



# E-mini instant water heater MCX Installation

Example of an **open-outlet** installation


Measurements in mm

Assembly and operating instructions must be observed upon installation


Using the aerator (included)

MCX 3..7: **CSP 3** 

MCX 6/7: **CSP 6** 



Alternative installation with **closed-outlet** tap.



**Push-button control panel**

The control panel with the sensor button and three colour LEDs is used to set the outlet water temperature to 35°C, 38°C or 45°C.





**Accessory for undersink installation** (included)

**FVS**

Flexible connecting hose  $\frac{3}{8}$  inch cap nut  $\times$   $\frac{3}{8}$  inch cap nut,  
length 50 cm

Part no. 89620

**T-piece**

Special T-connector  $\frac{3}{8}$  inch cap nut  $\times$   $\frac{3}{8}$  inch angle valve 10 mm

Part no. 89610



**Aerator CSP 3 or CSP 6** (included)

The aerator at the tap supports the energy- and water-saving operation of the compact instant water heater. The new special CSP aerators mix air into the water and thus create a uniform water stream that does not splatter but softly cascades down.

Aerator insert for tap adapter M22/24 at the tap

**CSP 3 (< 2 l / min):** Part no. 0010-00421

**CSP 6 (< 3.5 l / min):** Part no. 0010-00461



**FX** (optional)

In addition to user controls directly at the unit, the remote control allows for convenient temperature adjustment of the instant water heater at interior distances of up to 10 meters. Secure, bidirectional wireless transfer, continuous two-button temperature selection, two pre-set buttons and a LCD display, magnetic wall holder and batteries included. IP 20.

Dimensions (H  $\times$  W  $\times$  D): 5.8  $\times$  12.5  $\times$  1.9 cm

**FX:** Part no. 2400-26090