





Produto: Ligações Flexíveis em Malha de Aço Inox – DN8 – UNE 53626-2

Product: Flexible Hose Stainless Braid – DN8 – UNE 53626-2

Configurações:

Settings:

| | | | | | | | |
|---|-------------------------|---|-------------------------|---|-------------------------|---|-------------------------|
|  | Fêmea 3/8 Female 3/8 |  | Fêmea 3/8 Female 3/8 |  | Fêmea 3/8 Female 3/8 |  | Fêmea 3/8 Female 3/8 |
| | Fêmea 1/2 Female 1/2 | | Fêmea 1/2 Female 1/2 | | Fêmea 1/2 Female 1/2 | | Fêmea 1/2 Female 1/2 |
| | Macho 3/8 Male 3/8 | | Macho 3/8 Male 3/8 | | Macho 3/8 Male 3/8 | | Macho 3/8 Male 3/8 |
| Fêmea 1/2 Female 1/2 | Macho 1/2 Male 1/2 | Fêmea 3/8 Female 3/8 | Macho 1/2 Male 3/8 | Bicorne Ø 10 | Macho 1/2 Male 1/2 | Monobloco M10x1 | Macho 1/2 Male 3/8 |

Comprimentos (m):

Lengths (m)

| | | | | | | |
|------|------|------|------|------|------|------|
| 0,15 | 0,20 | 0,25 | 0,30 | 0,35 | 0,40 | 0,45 |
| 0,50 | 0,60 | 0,70 | 0,80 | 0,90 | | |
| 1,00 | 1,25 | 1,50 | 1,75 | 2,00 | | |

| | | | |
|------|------|------|------|
| 0,30 | 0,35 | 0,40 | 0,45 |
| 0,50 | 0,60 | 0,70 | 0,80 |

Pressão Máxima de Trabalho: 20 bar

Maximal Working pressure: 20 bar

Temperatura Máxima: 90 °C

Maximal Temperatura: 90 °C

Raio Mínimo de Curvatura: 30mm

Minimum bending radius: 30mm

Produto Certificado:

Product Certified:



PT/ UNE 53626/ 09/02894

Componentes de construção/Matéria-prima:

| | Componente | Matéria-prima |
|---|--|--|
|  | 1 Terminais Roscado Threaded Fittings | Latão CW614N Niquelado Brass CW614N Nickel Plated |
| | 2 Vedante Sealant | Borracha EPDM EPDM Rubber |
| | 3 Ponteira Nipple Fitting | Latão CW614N Brass CW614N |
| | 4 Casquilho Cravado Cap | Aço Inox DIN 1.4301 Stainless Steel DIN 1.4301 |
| | 5 Tubo Interior Inner Tube | Borracha EPDM EPDM Rubber |
| | 6 Malha de Revestimento Braided | Fio de Aço Inox AISI 304 DIN 1.4301 Stainless Steel Wire DIN 1.4301 |

Elaborado:

Data:

Aprovado:

Data:

1/1